

**RADIATOR PERFORMANCE DATA**

**SEPTEMBER 21, 2020**

For Help Desk Phone Numbers [Click here](#)

Component Performance Number: DM9989

**Radiator Data**

Radiator Part Number: 3249510  
 Radiator Type: 2.97CT  
 Front Area: 2.91 ft<sup>2</sup>  
 Radiator Dry Weight: 13.2 lbs  
 Radiator Wet Weight: NA lbs  
 Radiator Water Capacity High Temp Circuit: 1.0 gal  
 Radiator Water Capacity Low Temp Circuit: NA gal  
 Center of Gravity (X): 2.44 in (Distance from front face of core)  
 Center of Gravity (Y): 14.17 in (Distance from bottom of radiator support)  
 Center of Gravity (Z): 0.00 in (Distance from center line of core)

**Engine Data**

Performance Number: P3454A  
 Sales Model: C4.4 DITA  
 EKW: 50  
 Rating: STANDBY  
 Speed: 1800  
 Settings: NA  
 AC Temp Deg F: 210


**Combination Data**

Pully Ratio: 1.25  
 Fan Power: 2.68204 hp

Ambient Restrictions (1/2 inH2O)			Ambient Restrictions (3/4 inH2O)		
984 Feet	2460 Feet	4921 Feet	984 Feet	2460 Feet	4921 Feet
----- Max Ambient Pre-alarm Deg F -----					
141	136	127	140	134	125

Air Flow Restrictions (1/2 inH2O)	Air Flow Restrictions (3/4 inH2O)
4732	4555

CORE RESIST inH2O	CORE AIRFLOW scfm
0.11	1,024.13
0.31	2,051.78
0.57	3,075.91
0.87	4,103.57



**Reference**

Number: DM9989

No notes found...

**Parameters**

Reference: TM6016

## RADIATOR CORE DATA:

FOR OPEN GENERATOR SET ELECTRIC POWER APPLICATIONS, CORE AIR FLOW RESISTANCE DATA INCLUDES ENGINE, GENERATOR, AND COOLING PACKAGE. ADDITIONAL AIRFLOW RESISTANCE DUE TO CUSTOMER SUPPLIED ITEMS SUCH AS INLET/EXHAUST LOUVERS, SOUND ATTENUATION, OR INLET/EXHAUST AIR PIPEWORK IS NOT INCLUDED.

ALL OTHER APPLICATIONS OUTSIDE OF OPEN ELECTRIC POWER, CORE AIR FLOW RESISTANCE IS FOR FREE STANDING CORE ONLY.

CORE PERFORMANCE DATA IS BASED ON AN AIR DENSITY OF 1.20 KG/M3 (0.075 LB/CU FT)

## AMBIENT CAPABILITY:

AMBIENT CAPABILITY AND ALTITUDE CAPABILITY LISTED ON THIS PAGE REFLECTS THE CAPABILITY OF THE COOLING SYSTEM AT THE MAXIMUM GENERATOR RATING. AMBIENT CAPABILITY FOR STANDBY AND MISSION CRITICAL STANDBY RATINGS REPORTED AGAINST A JACKET WATER ENGINE EXIT TEMPERATURE LIMIT OF 104C (219F). ALL OTHER RATINGS REPORTED AT 99C (210F).

AMBIENT AND ALTITUDE CAPABILITY MUST BE VERIFIED FOR THE ENGINE AND GENERATOR IN THE ENGINE PERFORMANCE SECTION OF TMI.

NON TIER 4 EMISSION RATINGS ASSUME 4C (7F) AIR TO CORE RISE, TIER 4 EMISSION RATINGS ASSUME 6C (9F).

ALL PERFORMANCE SHOWN WITH 50/50 GLYCOL COOLANT.

LAST UPDATED: 09/11/2020

---

Caterpillar Confidential: **Green**

Content Owner: Commercial Processes Division

Web Master(s): [PSG Web Based Systems Support](#)

Current Date: 9/21/2020, 10:52:52 AM

© Caterpillar Inc. 2020 All Rights Reserved.

[Data Privacy Statement](#).