

OPEN SET					
MODEL	VOLTAGE	WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
DG175	240V, 1Ø	2,463 kg (5,429 lbs)	1,721 (67.8)	703 (27.7)	615 (24.2)
DG175	600V	2,469 kg (5,442 lbs)	1,719 (67.7)	703 (27.7)	
DG200	208V, 240V, 480V	2,477 kg (5,460 lbs)	1,716 (67.6)	702 (27.6)	

STD ENCLOSURE, STEEL					
MODEL	VOLTAGE	WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
DG175	240V, 1Ø	2,907 kg (6,409 lbs)	1,818 (71.6)	772 (30.4)	577 (22.7)
DG175	600V	2,913 kg (6,422 lbs)	1,816 (71.5)	772 (30.4)	
DG200	208V, 240V, 480V	2,921 kg (6,440 lbs)	1,814 (71.4)	771 (30.4)	

STD ENCLOSURE, ALUMINUM			
WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
2,696 kg (5,943 lbs)	1,810 (71.3)	753 (29.6)	577 (22.7)
2,702 kg (5,956 lbs)	1,808 (71.2)	752 (29.6)	
2,710 kg (5,974 lbs)	1,805 (71.1)	752 (29.6)	

LIA ENCLOSURE, STEEL					
MODEL	VOLTAGE	WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
DG175	240V, 1Ø	3,045 kg (6,713 lbs)	1,749 (68.9)	785 (30.9)	578 (22.8)
DG175	600V	3,051 kg (6,726 lbs)	1,748 (68.8)	785 (30.9)	
DG200	208V, 240V, 480V	3,059 kg (6,744 lbs)	1,745 (68.7)	784 (30.9)	

LIA ENCLOSURE, ALUMINUM			
WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
2,755 kg (6,074 lbs)	1,782 (70.2)	763 (30.0)	579 (22.8)
2,761 kg (6,087 lbs)	1,780 (70.1)	763 (30.0)	
2,769 kg (6,104 lbs)	1,777 (70.0)	762 (30.0)	

L2A ENCLOSURE, STEEL					
MODEL	VOLTAGE	WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
DG175	240V, 1Ø	3,152 kg (6,949 lbs)	1,836 (72.3)	879 (34.6)	580 (22.8)
DG175	600V	3,158 kg (6,962 lbs)	1,834 (72.2)	878 (34.6)	
DG200	208V, 240V, 480V	3,166 kg (6,980 lbs)	1,831 (72.1)	877 (34.5)	

L2A ENCLOSURE, ALUMINUM			
WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
2,801 kg (6,175 lbs)	1,829 (72.0)	821 (32.3)	581 (22.9)
2,807 kg (6,188 lbs)	1,829 (71.9)	820 (32.3)	
2,815 kg (6,206 lbs)	1,824 (71.8)	820 (32.3)	

L3A ENCLOSURE, STEEL					
MODEL	VOLTAGE	WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
DG175	240V, 1Ø	4,797 kg (10,575 lbs)	2,230 (87.8)	1,062 (41.8)	722 (28.4)
DG175	600V	4,801 kg (10,584 lbs)	2,228 (87.7)	1,062 (41.8)	
DG200	208V, 240V, 480V	4,809 kg (10,602 lbs)	2,226 (87.6)	1,061 (41.7)	

L3A ENCLOSURE, ALUMINUM			
WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
4,360 kg (9,612 lbs)	2,189 (86.2)	934 (36.8)	723 (28.5)
4,364 kg (9,620 lbs)	2,188 (86.1)	933 (36.7)	
4,372 kg (9,638 lbs)	2,185 (86.0)	932 (36.7)	

CENTER OF GRAVITY AND WEIGHT MAY CHANGE DUE TO UNIT OPTIONS

1			
2			
3			
4			
5			
6			
7			
8			

1	ES167A	INT-PROP
2	ES266B	IDENT
3	ES272D	DRAWING
4	ES098V	BRAND MARKINGS
5	ES0037	CONFIDENTIALITY
6	ES002A	INTERPRETATION
7	ES0001	INTPR & TOL
8	Caterpillar: Confidential Yellow	
9	From	RECORDS
10	SALES SPECIFIC SPECIFIED DIMENSIONS W/ TO, ARE BASED ON	SECONDARY X
11	THIRD ANGLE PROJECTION	SHEET 4 OF 4
12		REV. 10/2023
13	CATERPILLAR	
14	FOR NOTES SEE SHEET 1	
15	(SCALE: 1:30)	
16	555-6993 04	