OPEN SET					
MODEL	VOLTAGE	WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
DG230, 250	600V	2,669 kg (5,883 lbs)	1,874 (73.8)	690 (27.2)	668 (26.3)
DG230, 250	208V, 240V, 480V	2,677 kg (5,901 lbs)	1,871 (73.7)	690 (27.2)	
DG230, 250	600V (UPSIZE)	2,729 kg (6,015 lbs)	1,851 (72.9)	687 (27.1)	
DG230, 250	208V, 240V, 480V (UPSIZE)	2,736 kg (6,031 lbs)	1,849 (72.8)	687 (27.1)	

STD ENCLOSURE, STEEL					
MODEL	VOLTAGE	WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
DG230, 250	600V	3,378 kg (7,448 lbs)	1,999 (78.7)	810 (31.9)	634 (24.9)
DG230, 250	208V, 240V, 480V	3,386 kg (7,465 lbs)	1,997 (78.6)	809 (31.8)	
DG230, 250	600V (UPSIZE)	3,438 kg (7,580 lbs)	1,979 (77.9)	805 (31.7)	
DG230, 250	208V, 240V, 480V (UPSIZE)	3,445 kg (7,596 lbs)	1,977 (77.8)	805 (31.7)	

STD ENCLOSURE, ALUMINUM			
WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
3,018 kg (6,654 lbs)	1,966 (77.4)	762 (30.0)	628 (24.7)
3,026 kg (6,671 lbs)	1,963 (77.3)	761 (30.0)	
3,078 kg (6,786 lbs)	1,944 (76.5)	758 (29.8)	
3,085 kg (6,801 lbs)	1,942 (76.5)	758 (29.8)	

L1A ENCLOSURE, STEEL					
MODEL	VOLTAGE	WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
DG230, 250	600V	3,588 kg (7,911 lbs)	1,906 (75.0)	834 (32.8)	636 (25.0)
DG230, 250	208V, 240V, 480V	3,596 kg (7,928 lbs)	1,904 (75.0)	833 (32.8)	
DG230, 250	600V (UPSIZE)	3,648 kg (8,043 lbs)	1,889 (74.4)	829 (32.6)	
DG230, 250	208V, 240V, 480V (UPSIZE)	3,655 kg (8,059 lbs)	1,887 (74.3)	829 (32.6)	

L1A ENCLOSURE, ALUMINUM			
WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
3,108 kg (6,853 lbs)	1,920 (75.6)	776 (30.5)	630 (24.8)
3,116 kg (6,870 lbs)	1,917 (75.5)	775 (30.5)	
3,168 kg (6,985 lbs)	1,900 (74.8)	772 (30.4)	
3,175 kg (7,000 lbs)	1,897 (74.7)	771 (30.4)	

L2A ENCLOSURE, STEEL					
MODEL	VOLTAGE	WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
DG230, 250	600V	3,848 kg (8,484 lbs)	2,032 (80.0)	1,003 (39.5)	638 (25.1)
DG230, 250	208V, 240V, 480V	3,856 kg (8,502 lbs)	2,029 (79.9)	1,002 (39.5)	
DG230, 250	600V (UPSIZE)	3,908 kg (8,616 lbs)	2,014 (79.3)	996 (39.2)	
DG230, 250	208V, 240V, 480V (UPSIZE)	3,915 kg (8,632 lbs)	2,012 (79.2)	995 (39.2)	

L2A ENCLOSURE, ALUMINUM			
WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
3,220 kg (7,099 lbs)	1,985 (78.2)	867 (34.1)	631 (24.9)
3,228 kg (7,117 lbs)	1,983 (78.1)	867 (34.1)	
3,280 kg (7,231 lbs)	1,965 (77.3)	861 (33.9)	
3,287 kg (7,247 lbs)	1,962 (77.3)	861 (33.9)	

L3A ENCLOSURE, STEEL					
MODEL	VOLTAGE	WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
DG230, 250	600V	4,917 kg (10,840 lbs)	2,172 (85.5)	1,085 (42.7)	722 (28.4)
DG230, 250	208V, 240V, 480V	4,925 kg (10,857 lbs)	2,169 (85.4)	1,083 (42.6)	
DG230, 250	600V (UPSIZE)	4,977 kg (10,972 lbs)	2,155 (84.8)	1,079 (42.5)	
DG230, 250	208V, 240V, 480V (UPSIZE)	4,984 kg (10,990 lbs)	2,153 (84.8)	1,080 (42.5)	

L3A ENCLOSURE, ALUMINUM			
WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
4,458 kg (9,828 lbs)	2,132 (83.9)	948 (37.3)	717 (28.2)
4,466 kg (9,846 lbs)	2,130 (83.9)	948 (37.3)	
4,518 kg (9,960 lbs)	2,115 (83.3)	953 (37.5)	
4,525 kg (9,976 lbs)	2,113 (83.2)	954 (37.6)	

CENTER OF GRAVITY AND WEIGHT MAY CHANGE DUE TO UNIT OPTIONS

FOR NOTES SEE SHEET 1
(SCALE : 1:30)

1E5167A	INT-PROP
1E2966B	IDENT
1E2722D	DRAWING
1E0196V	BRAND MARKINGS
1E0013Y	CONFIDENTIALITY
1E0012A	INTERPRETATION
1E0011	INTPR & TOL

Caterpillar: Confidential Yellow

PROG. | CHECK RECORDS

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN mm DIMENSIONS W/O TOL ARE BASIC

REVISION TYPE: PRIMARY X SECONDARY

THIRD ANGLE PROJECTION

SHEET 3 of 4

DWG CONTROL W923

CATERPILLAR

THE INFORMATION HERE IN THIS DRAWING IS PROPRIETARY TO CATERPILLAR INC. IT IS PROVIDED IN CONFIDENCE AND MUST NOT BE DISCLOSED TO OTHERS OR REPRODUCED IN ANY FORM WITHOUT THE WRITTEN PERMISSION OF CATERPILLAR INC.

INSTALLATION
(14.2 L OPEN)

555-6994 | VER: - | CHG: 06 | E