

OPEN SET					
MODEL	VOLTAGE	WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
DG 275	208V, 240V, 480V 600V	2,722 kg (6,000 lbs) 2,715 kg (5,985 lbs)	1,833 (72.2) 1,846 (72.7)	751 (29.6)	671 (29.6)
DG 275	208V, 240V, 480V 600V (UPSIZE)	2,822 kg (6,200 lbs) 2,852 kg (6,280 lbs)	1,799 (70.8) 1,789 (70.4)	752 (29.6)	
DG 300	208V, 240V, 480V 600V	2,822 kg (6,200 lbs) 2,852 kg (6,280 lbs)	1,799 (70.8) 1,789 (70.4)	752 (29.6)	

STD ENCLOSURE, STEEL					
MODEL	VOLTAGE	WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
DG 275/300	208V, 240V, 480V	3,425 kg (7,535 lbs)	1,975 (77.8)	853 (33.6)	678 (26.7)
DG 275/300	600V	3,432 kg (7,550 lbs)	1,965 (77.4)	853 (33.6)	
DG 275	208V, 240V, 480V (UPSIZE)	3,425 kg (7,535 lbs)	1,975 (77.8)	853 (33.6)	
DG 275	600V (UPSIZE)	3,432 kg (7,550 lbs)	1,965 (77.4)	853 (33.6)	

STD ENCLOSURE, ALUMINUM			
WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
3,065 kg (6,743 lbs)	1,939 (76.3)	813 (32.0)	679 (26.7)
3,172 kg (6,758 lbs)	1,894 (74.6)	811 (31.9)	
3,072 kg (6,758 lbs)	1,928 (75.9)	813 (32.0)	
3,202 kg (7,044 lbs)	1,885 (74.2)	811 (31.9)	

LIA ENCLOSURE, STEEL					
MODEL	VOLTAGE	WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
DG275, 300	208V, 240V, 480V	3,532 kg (7,770 lbs)	1,934 (76.1)	850 (33.5)	678 (26.7)
DG275, 300	600V	3,562 kg (7,836 lbs)	1,925 (75.8)	850 (33.5)	
DG275	208V, 240V, 480V (UPSIZE)	3,532 kg (7,770 lbs)	1,934 (76.1)	850 (33.5)	
DG275	600V (UPSIZE)	3,562 kg (7,836 lbs)	1,925 (75.8)	850 (33.5)	

LIA ENCLOSURE, ALUMINUM			
WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
3,155 kg (6,941 lbs)	1,895 (74.6)	825 (32.5)	678 (26.7)
3,262 kg (7,176 lbs)	1,853 (73.0)	823 (32.4)	
3,162 kg (6,957 lbs)	1,884 (74.1)	825 (32.5)	
3,292 kg (7,242 lbs)	1,845 (72.6)	822 (32.4)	

L2A ENCLOSURE, STEEL					
MODEL	VOLTAGE	WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
DG275, 300	208V, 240V, 480V	4,002 kg (8,804 lbs)	1,973 (77.7)	1,029 (40.5)	677 (26.7)
DG275, 300	600V	4,032 kg (8,870 lbs)	1,965 (77.4)	1,027 (40.4)	
DG275	208V, 240V, 480V (UPSIZE)	4,002 kg (8,804 lbs)	1,973 (77.7)	1,029 (40.5)	
DG275	600V (UPSIZE)	4,032 kg (8,870 lbs)	1,965 (77.4)	1,027 (40.4)	

L2A ENCLOSURE, ALUMINUM			
WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
3,267 kg (7,187 lbs)	1,960 (77.2)	912 (35.9)	678 (26.7)
3,374 kg (7,423 lbs)	1,917 (75.5)	907 (35.7)	
3,274 kg (7,203 lbs)	1,949 (76.7)	912 (35.9)	
3,404 kg (7,490 lbs)	1,908 (75.1)	905 (35.6)	

L3A ENCLOSURE, STEEL					
MODEL	VOLTAGE	WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
DG275, 300	208V, 240V, 480V	5,025 kg (11,080 lbs)	2,116 (83.3)	1,054 (41.5)	740 (29.1)
DG275, 300	600V	5,055 kg (11,144 lbs)	2,108 (82.9)	1,051 (41.4)	
DG275	208V, 240V, 480V (UPSIZE)	5,025 kg (11,080 lbs)	2,116 (83.3)	1,054 (41.5)	
DG275	600V (UPSIZE)	5,055 kg (11,144 lbs)	2,108 (82.9)	1,051 (41.4)	

L3A ENCLOSURE, ALUMINUM			
WEIGHT	CENTER OF GRAVITY DIM. X	CENTER OF GRAVITY DIM. Y	CENTER OF GRAVITY DIM. Z
4,589 kg (10,118 lbs)	2,056 (80.9)	935 (36.8)	741 (29.2)
4,619 kg (10,183 lbs)	2,097 (82.5)	932 (36.7)	
4,589 kg (10,118 lbs)	2,056 (80.9)	935 (36.8)	
4,619 kg (10,183 lbs)	2,097 (82.5)	932 (36.7)	

CENTER OF GRAVITY AND WEIGHT MAY CHANGE DUE TO UNIT OPTIONS

1			
2			
3			
4			
5			
6			
7			
8			
9			
10			
11			
12			
13			
14			
15			
16			
17			
18			
19			
20			
21			
22			
23			
24			
25			
26			
27			
28			
29			
30			
31			
32			
33			
34			
35			
36			
37			
38			
39			
40			
41			
42			
43			
44			
45			
46			
47			
48			
49			
50			
51			
52			
53			
54			
55			
56			
57			
58			
59			
60			
61			
62			
63			
64			
65			
66			
67			
68			
69			
70			
71			
72			
73			
74			
75			
76			
77			
78			
79			
80			
81			
82			
83			
84			
85			
86			
87			
88			
89			
90			
91			
92			
93			
94			
95			
96			
97			
98			
99			
100			

1 ES167A INT-PROP
 2 ES266B IDENT
 3 ES272D DRAWING
 4 ES019W BRAND MARKINGS
 5 ES0037 CONFIDENTIALITY
 6 ES002A INTERPRETATION
 7 ES0001 INTRP & TOL
 8 Caterpillar: Confidential Yellow
 9 From RECORDED
 10 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
 11 THIRD ANGLE PROJECTION SHEET 4 OF 4
 12 10/2023
CATERPILLAR
 13
 14
 15
 16
 17
 18
 19
 20
 21
 22
 23
 24
 25
 26
 27
 28
 29
 30
 31
 32
 33
 34
 35
 36
 37
 38
 39
 40
 41
 42
 43
 44
 45
 46
 47
 48
 49
 50
 51
 52
 53
 54
 55
 56
 57
 58
 59
 60
 61
 62
 63
 64
 65
 66
 67
 68
 69
 70
 71
 72
 73
 74
 75
 76
 77
 78
 79
 80
 81
 82
 83
 84
 85
 86
 87
 88
 89
 90
 91
 92
 93
 94
 95
 96
 97
 98
 99
 100

FOR NOTES SEE SHEET 1 (SCALE = 1:30)